

ICMA[®]

NEW ARRIVAL



100%
Made in Italy

NEW PRODUCT LINE

BALL VALVES

EN

Icma introduces a new full bore **"Ball Valves line"**.


A sturdy and reliable product, available at extremely competitive price.

Suitable for water and non dangerous gas in heating, cooling, pneumatic and systems.

100% "Made in Italy" Design and manufacturing.



FULL
BORE



MAX
TEMPERATURE
150°



MAX
OPERATING
PRESSURE
from PN25 to PN50



LEVER
HANDLE



O-RING STEM:
NBR
Viton[®]



PTFE
SEAT
GASKETS



ISO
CONNECTION
THREAD 228/1



ART.215



Full bore ball valve with pipe tail, red/blue coated Aluminum T-handle, flat seat connection. double o-ring anti-blow out stem. Flat seat tail makes these valves perfect for underfloor heating system.

BALL: CW617N-UNIEN12165-CHROMEPLATED

SEAT GASKET: PTFE

BODY: CW617N - UNI EN 12165

SLEEVE: CW617N - UNI EN 12165

STEM: CW614N - UNI EN 12164/CW67

O-RING: NBR; Viton®

HANDLE: RED/BLUE ALUMINUM COATED ● ●

NUT: ZINC PLATED STEEL

PIPE JUNCTION: CW617N - UNI EN 12165

O-RING: EPDM PEROX

GASKET: EPDM PEROX

ART.347



Full bore ball valve with pipe tail, red/white coated Aluminum T-handle, M/F connection thread, double o-ring anti-blow out stem.

BALL: CW617N-UNIEN12165-CHROMEPLATED

SEAT GASKET: PTFE

BODY: CW617N - UNI EN 12165

SLEEVE: CW617N - UNI EN 12165

STEM: CW614N - UNI EN 12164/CW67

O-RING: NBR; Viton®

HANDLE: RED/WHITE COATED ALUMINUM ● ○

NUT: ZINC PLATED STEEL

PIPE JUNCTION: CW617N - UNI EN 12165

O-RING: EPDM PEROX

ART.348



Full bore ball valve with pipe tail, red/white coated Aluminum T-handle, M/F connection thread, double o-ring anti-blow out stem.

BALL: CW617N-UNIEN12165-CHROMEPLATED

SEAT GASKET: PTFE

BODY: CW617N - UNI EN 12165

SLEEVE: CW617N - UNI EN 12165

STEM: CW614N - UNI EN 12164/CW67

HANDLE: RED/WHITE COATED ALUMINUM ● ○

NUT: ZINC PLATED STEEL

O-RING: NBR; Viton®

PIPE JUNCTION: CW617N - UNI EN 12165

GASKET: EPDM PEROX

ART.349



Full bore ball valve, red coated Aluminum T-handle, F/F connection thread, double o-ring anti-blow stem.

BALL: CW617N-UNIEN12165-CHROMEPLATED

SEAT GASKET: PTFE

BODY: CW617N - UNI EN 12165

SLEEVE: CW617N - UNI EN 12165

STEM: CW614N - UNI EN 12164

O-RING: NBR; Viton®

HANDLE: RED COATED ALUMINUM ●

NUT: ZINC PLATED STEEL

ART.350



Full bore ball valve, red coated Aluminum T-handle, F/F connection thread, double o-ring anti-blow stem.

BALL: CW617N-UNIEN12165-CHROMEPLATED

SEAT GASKET: PTFE

BODY: CW617N - UNI EN 12165

SLEEVE: CW617N - UNI EN 12165

STEM: CW614N - UNI EN 12164

O-RING: NBR; Viton®

HANDLE: RED COATED ALUMINUM ●

NUT: ZINC PLATED STEEL

ART.351



Full bore ball valve, red coated Aluminum T-handle, M/F connection thread, double o-ring anti-blow stem.

BALL: CW617N-UNIEN12165-CHROMEPLATED

SEAT GASKET: PTFE

BODY: CW617N - UNI EN 12165

SLEEVE: CW617N - UNI EN 12165

STEM: CW614N - UNI EN 12164

O-RING: NBR; Viton®

HANDLE: RED COATED ALUMINUM ●

NUT: ZINC PLATED STEEL

ART.352



Full bore ball valve, red coated Aluminum T-handle, M/F connection thread, double o-ring anti-blow stem.

BALL: CW617N-UNIEN12165-CHROMEPLATED

SEAT GASKET: PTFE

BODY: CW617N - UNI EN 12165

SLEEVE: CW617N - UNI EN 12165

STEM: CW614N - UNI EN 12164

O-RING: NBR; Viton®

HANDLE: RED COATED ALUMINUM ●

NUT: ZINC PLATED STEEL

ART.361



Full bore angle ball valve, red/white coated Aluminum T-handle, M/F connection thread, double o-ring anti-blow out stem.

BALL: CW617N-UNIEN12165-CHROMEPLATED

SEAT GASKET: PTFE

BODY: CW617N - UNI EN 12165

SLEEVE: CW617N - UNI EN 12165

STEM: CW614N - UNI EN 12164

O-RING: NBR; Viton®

HANDLE: RED/WHITE COATED ALUMINUM ● ○

NUT: ZINC PLATED STEEL

GASKET: EPDM PEROX

ART.362



Full bore angle ball valve, red/white coated Aluminum T-handle, M/F connection thread, double o-ring anti-blow out stem.

BALL: CW617N-UNIEN12165-CHROMEPLATED

SEAT GASKET: PTFE

BODY: CW617N - UNI EN 12165

SLEEVE: CW617N - UNI EN 12165

STEM: CW614N - UNI EN 12164

O-RING: NBR; Viton®

HANDLE: RED/WHITE COATED ALUMINUM ● ○

NUT: ZINC PLATED STEEL

GASKET: EPDM PEROX

ART.225



Full bore angle ball valve, red/blue coated Aluminum T-handle, M/F connection thread, double o-ring anti-blow out stem.

BALL: CW617N-UNIEN12165-CHROMEPLATED

SEAT GASKET: PTFE

BODY: CW617N - UNI EN 12165

SLEEVE: CW617N - UNI EN 12165

STEM: CW614N - UNI EN 12164 O-RING: NBR; Viton®

O-RING: NBR; Viton®

HANDLE: RED/BLUE COATED ALUMINUM ● ●

NUT: ZINC PLATED STEEL

GASKET: EPDM PEROX

ART.215 Cod: 87215AF11 Size: 1" ●
Cod: 87215AF12 Size: 1" ●

ART.347 Cod: 87347AD11 Size: 1/2" ●
Cod: 87347AE11 Size: 3/4" ●
Cod: 87347AF11 Size: 1" ●
Cod: 87347AG11 Size: 1"1/4" ●
Cod: 87347AD13 Size: 1/2" ○
Cod: 87347AE13 Size: 3/4" ○

ART.348 Cod: 87348AD11 Size: 1/2" ●
Cod: 87348AE11 Size: 3/4" ●
Cod: 87348AD13 Size: 1/2" ○
Cod: 87348AE13 Size: 3/4" ○

ART.349 Cod: 87349AC11 Size: 3/8" ●
Cod: 87349AD11 Size: 1/2" ●
Cod: 87349AE11 Size: 3/4" ●
Cod: 87349AF11 Size: 1" ●
Cod: 87349AG11 Size: 1"1/4" ●

ART.350 Cod: 87350AC11 Size: 3/8" ●
Cod: 87350AD11 Size: 1/2" ●
Cod: 87350AE11 Size: 3/4" ●
Cod: 87350AF11 Size: 1" ●
Cod: 87350AG11 Size: 1"1/4" ●
Cod: 87350AH11 Size: 1"1/2" ●
Cod: 87350AJ11 Size: 2" ●

ART.351 Cod: 87351AC11 Size: 3/8" ●
Cod: 87351AD11 Size: 1/2" ●
Cod: 87347AD11 Size: 3/4" ●
Cod: 87351AE11 Size: 1" ●
Cod: 87351AF11 Size: 1"1/4" ●

ART.352 Cod: 87352AC11 Size: 3/8" ●
Cod: 87352AD11 Size: 1/2" ●
Cod: 87352AE11 Size: 3/4" ●
Cod: 87352AF11 Size: 1" ●
Cod: 87352AG11 Size: 1"1/4" ●
Cod: 87352AH11 Size: 1"1/2" ●
Cod: 87352AJ11 Size: 2" ●

ART.361 Cod: 87361AD11 Size: 1/2" ●
Cod: 87361AE11 Size: 3/4" ●
Cod: 87361AE11 Size: 1" ●
Cod: 87361AD13 Size: 1/2" ○
Cod: 87361AE13 Size: 3/4" ○

ART.362 Cod: 87362AD11 Size: 1/2" ●
Cod: 87362AE11 Size: 3/4" ●
Cod: 87362AD13 Size: 1/2" ○
Cod: 87362AE13 Size: 3/4" ○

ART.225 Cod: 87225AF11 Size: 1" ●
Cod: 87225AF12 Size: 1" ●