

### / Description

The Neutralizer 762 is a device designed for an easy installation on the condensation drain of the new condensing boilers. The 762 is able to solve the problem of acid wastewater.

The environmental regulations of many countries impose waste waters with a pH of between 5,5 and 9,5.

The operating principle consists in flowing the drain water through spheres anti-clogging minerals that dissolve slowly and neutralize drain acidity.



### / Plus

- Simple and fast installation
- Sphere of alkaline granular anti-clogging
- Suitable for all condensing mural boilers up to 25 Kw
- Avoid the corrosion of the pipes
- Connection for condensate drain pipe d.12

### / Technical features

Compatible fluid:	Scarico condensa caldaia
Max pressure:	3 bar 300 kPa
Min/Max temperature (operating/ambient):	5 - 55 °C
Max capacity:	3 l/h
Mineral capacity:	110 g
Diameter:	45 mm
Length:	240 mm
Connections:	3/4" G+portagomma d. 12
Heating power:	Up to 25kW

### / Materials

Head:	ABS
Bowl	Trasparent SAN
Mineral	Spheres of alkaline granular

### / Accessories

- Fixing clip d. 50
- Hose connectors
  - 3/4" G M - d.12 straight
  - 3/4" G M - d.12 elbow
  - 3/4" G F - d.12 swivel straight